

Product information

Description and application:	Texture spray is particularly suited for refurbishing car body parts made of plastic. Easy to process, good adhesion properties, very fast drying, resistant to scratching. Processing: sand the damage area, if necessary use a filler and then apply a thin coat of plastic bonding agent. Shake the can for at least 2 minutes. Test spray to check compatibility and colour tone. Apply 2 - 3 spray coats allowing 5-10 minutes between each coat. Can be painted over using all standart 1K and 2K top coats after around 15 minutes at 20 °C. Do not spray on surfaces coated with synthetic resins as the paint may lift
Product benefits:	Easy to process. Good adhesion. Economic. Fast drying. Scratch resistant. Free of heavy metals: no lead, cadmium, chrome.
Binding agent base:	Nitro combination resins.
Spraying coating:	2 cross-coats: approx. 40 - 50 µm dry film thickness
Drying times:	Dust dry: after approx. 30 min. Fast to handling: after approx. 1 hour Dry hard: after approx. 24 hours
Can be painted over:	With itself: after 15 minutes.
Paints structure:	Spray directly onto the primer coated surface.
Storage:	Protect from sunlight and do not expose to temperature exceeding +50°C. We guarantee shelf life and quality of the product not less than 3 years.
Packaging:	400 ml
Colour:	Black
Notes:	Turn the can around after use and spray the valve until it is empty.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.