

Product information

Description and application:	1K Kontrol spray based on nitrocellulose in combination with special alkyd resins. Excellent adhesion to metal surfaces, glass, ceramics, various types of plastic, wood. Black guide coat used to make irregularities visible once the putty and filler has been applied and prepared for the following sanding. It makes irregularities on the surface clearly visible. Sanding over the area intensifies the effect. Shake can well for 2 minutes.
Product benefits:	Easy running. High level of solid matter. Very economic. Rapid tack-drying and good drying properties. Scratch resistant. Light-fast and weather resistant.
Spraying distance:	15 – 20 cm
Spraying coating:	Apply 2 - 3 coats: ca. 40 - 60 µm. Meet an intermediate flash-off time of 5 min between two spray-passes.
Drying times:	The followings drying-times refer to a dry film thickness of 40 µm and an ambient temperature of 20 °C. Dust free: after 5 - 10 min. Hard dry: after 24 h.
Pre-treatment:	Sand and degrease the surface thoroughly. Apply only a dust-free and dry substrates.
VOC:	EU limit value for this product (Cat B / e.): 840 g / l (2007). This product has VOC max. <820 g / l.
Storage:	The description of the shelf life refers to an unused can being stored appropriately at a temperature of 15 to 25 °C and a relative humidity beneath 60%. We guarantee shelf life and quality of the product not less than 5 years.
Packaging:	400 ml
Color / Gloss level:	Black / Matt
Notes:	Turn the can around after use and spray the valve until it is empty.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.