

Product information

Product description:	SOLL BODY CAVITY PROTECTION AEROSOL is an anti-corrosion product based on modified petroleum, especially developed for the inside protection of cars. The product provides excellent resistance to common road conditions, salt, moisture and general corrosive atmosphere. It has strong penetrating properties so that difficult accessible parts of the bodywork such as (welding) seams can be conserved. It should be applied to the inside of box panels, headlight wells taillight well etc. It provides a non-drying, tack-free coating on metals with long term corrosion protection.		
Properties:	Good anti corrosion protection, excellent “penetrating & creep” properties, easy application, Resistant to water, brine, acids and alkaline. It doesn’t corrode plastics, rubbers, and paints. When regularly used it can effectively prevent and even stop corrosion in cavities.		
Application:	Developed as corrosion protective coating in box sections of cars, truck, boats, trailers, campers ect., such as insides of doors, inside side panels, inside motor hoods and trunk, the inside of chassis bars ect. Do not apply on parts of the braking system or on parts of the exhaust system. Product can also be use on sheets of metals, tools and machinery during storage.		
Directions for use:	For the treatment of cavities a special actuator with long tube and around spraying nozzle can be used.		
Technical information:			
Base:	Modified petrolatum, sulfonates, oil, solvents pigment and additives		
Color:	Brown, transparent		
Odour:	Typical		
Density (20 °C):	0,66 g/cm³ (aerosol), 0,8 g/cm³ (active agent)		
Viscosity (20 °C):	Ready to spray aerosol		
Salt spray test, SS DIN 50021, 700 hour	100 µm dry layer	Rust: according DIN 53 210 → Ri 0 Blistering: according DIN 53 209 → m0/g0	
Recommended layer thickness / Use	100 µm wet, 30 µm dry / 1 l per 5 m²		
Application temperature:	10 °C to 25 °C		
Temperature resistance of the coating:	- 30 °C to 80 °C		
Drying time: depends on temperature, ventilation and layer thickness.	30 mu wet layer: 20 ⁰ C + ventilation	Dust dry: ca. 1 hour Touch dry: ca. 3 hours	
Solids:	16 % (aerosol), 30 % (active agent)		
Directions before use:	Shake the can well before use. Surface must be dry and clean, free from dirt, rust, grease ect. (Dry) parts of product can be removed with terpentine.		
Storage:	Store in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.		
Shelf life:	12 months in original and unopened packaging.		
All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.			