

DESCRIPTION

SOLL primer provides a fast and reliable adhesion of glue to the window glass.

APPLICATION

Clean the edges of the glass with the SOLL silicon remover. Apply the SOLL glass primer on the glass edge with the applicator and leave to dry for minimum 10 minutes. Apply the car glass adhesive with a hand or pneumatic gun to the car body flange. Place and press the glass slightly to the car body flange and adjust the pressure and support on distancing blocks.

PHYSICAL PROPERTIES

General description:	mixture of polyisocyanates in an organic solvents
Colour:	black
Form:	liquid
Boiling temperature:	79 °C
Flash point:	8 °C
Self-ignition:	> 200 °C (it does not self-ignite in ambient temperature)
Density:	1,0 g / cm ³
Explosive limit:	upper: 11.5 % vol. / lower: 1.8 % vol.

STORAGE AND SHELF LIFE

Store in well sealed containers in a dry and cool place, away from fire and heat sources, including direct sunlight. Shelf life: 12 months if stored in tightly closed original packaging.

SAFETY PRECAUTIONS

Please see our latest Safety data sheet for details.

TRANSPORT CLASSIFICATION

Please see our latest Safety data sheet for details.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.
