



MEDIUM COMPOUND **SOLL MEDIUM 75**

Product information

Purpose of Use

For fast removal of defects (holes, surface roughness and etc.) on a fresh coat of paint applied during the repair and on a hardened covering coat of (priming) paint. Also suitable for removal of deep scratches and repair of extremely worn-out paint.

Application:

For any varnished car, ship or wood surfaces (for solvent-based varnish, one-component or multi-component systems, water-based varnish, powdered varnish and scratch-resistant transparent varnish). Do not use for matted varnish.

Composition:

Aluminium oxides, hydrocarbons, water, silicone-free

Physiological Properties

When the polishing compound is used in accordance with the specified terms of use is chemically safe.

Use

Moving recommended polishing discs around or outwards.

Attention

In order to ensure a scratch-free surface, do not use the grinding paste with other polishes or solvents. Otherwise the warranty will not be valid.

Shelf Life

24 months, if kept in the original packaging at 15 - 25°C temperature. Keep away from direct sunlight and freezing temperatures during the storage and transportation.

Packaging

Art. Nr:	Volume
SPP-75	1 kg

We provide oral and written consultations about tested products and their technical use in a fair and competent way, which is not required for the protection of rights of third parties and means that it falls under your responsibility to test our products and determine whether they suit the intended method and purpose. The use or treatment of products is beyond our control and we do not assume responsibility for this. In case of any possible damage, we restrict ourselves only to the value of products provided to you for use. However, we can ensure excellent quality of products under the general conditions for sale and supply, which do not apply to tested products.